

NEW

EXCAVATOR MULCHERS

UML/S/EX/VT



from 110 to 200 HP



Ø 30 cm max



from 20 to 25 t

## FORESTRY MULCHER WITH FIXED TOOTH ROTOR FOR EXCAVATORS.

Specifically developed for excavators ranging from 20 - 25 tons. Using key design features, such as interchangeable counter-blades and other engineering advantages, it approaches the performance levels of our largest model the UMM/EX. Furthermore, the VT automatic variable displacement hydraulic motor increases efficiency. This allows the machine to carry out complex operations effortlessly while working on sides of the roads, along river banks and on steep slopes.

### STANDARD EQUIPMENT

- Enclosed machine body
- Belt transmission
- 110/60cc variable torque hydraulic piston motor
- Flow control valve
- Hydraulic hood
- Interchangeable counter blades
- Bolted, dual row protection chains
- Motor integrated into the frame
- Supporting service leg

### OPTIONS

- 160/115cc variable torque hydraulic piston motor
- Customized setting hydraulic motor
- Diverter valve
- Additional reinforced side plates
- Customized attachment bracket
- Customized attachment bracket with fixed thumb
- Multiple tooth options

## FEATURES



**Hydraulic controlled hood**  
revolutionary system for door opening/closing that prevents dirt from entering into the service areas of the machine

**Forged and hardened interchangeable counter-blades**  
for the maximum duration

**Oversized hubs and bearings**

**Motor enclosed in frame**  
protected from dirt and damage

**VT motor**  
Adjustable motor to obtain the maximum performance out of any excavator

**Dual row protection chains**  
deflects debris exiting the machine, increasing safety

**VT variable torque motor**  
to increase performance and reduce operating costs



## MAIN OPTIONS



**1 Customized attachment bracket**



**2 Diverter valve**  
to control the opening and closing of the hydraulic door



**3 Additional reinforced side plates**  
for extreme conditions



**4 Customized attachment bracket with fixed thumb**

| MODEL           | Power (HP) |     | Flow rate (L/min) |     | Pressure (bar) |     | Excavator weight (t.) |     | Working width (mm) | Weight (kg) | Max shredding diameter (mm) | No. teeth  |          |
|-----------------|------------|-----|-------------------|-----|----------------|-----|-----------------------|-----|--------------------|-------------|-----------------------------|------------|----------|
|                 | min        | max | min               | max | min            | max | min                   | max |                    |             |                             | C/3+C/3/SS | I+C/3/SS |
| UML/S/EX/VT 125 | 110        | 200 | 150               | 300 | 220            | 350 | 20                    | 25  | 1350               | 1500        | 300                         | 26+4       | 36+2     |
| UML/S/EX/VT 150 | 110        | 200 | 150               | 300 | 220            | 350 | 20                    | 25  | 1590               | 1660        | 300                         | 32+4       | 42+2     |

Data refers to machine as standard. The technical data in this catalog may be altered without prior notice.



THE NEW REFERENCE POINT  
FOR 20 TO 25 TON EXCAVATORS